Technical information



Paint Express: HYDRO structuring pastes

Adding of different Structure pastes to both our HYDRO Colour lacquer systems **COOL-COLOR** HB 6528x(gloss level)-(colour tone) and PERFECT-COLOR HDB 5434x(gloss level)-(colour tone) achieves differing pearl structure effects.

The result is a pleasant feel and visually interesting effects. This lacquer system's already exceptional surface properties are further improved by the Structure additive with little extra effort.

This creates particularly scratch- and scrub resistant surfaces.

Materials required:

HZ 710 for a fine
HZ 720 for a medium and
HZ 750 for a coarse pearl structure

Base colour lacquer:

COOL-COLOR HB 6528x(gloss level)-(colour tone) or PERFECT-COLOR HDB 5434x(gloss level)-(colour tone)

Mixture details:

- 95.0 parts of the desired HYDRO Colour lacquer
- 5.0 parts of the corresponding Pearl Structure paste

This way modified colour lacquer should be additionally marked with "pearl effect".

Use:

- Stir all materials carefully before use.
- Stirring by hand ensures good incorporation of the Structure paste into the colour lacquer.
- If you use an agitator, please ensure that the material does not become foamy due to over-stirring.
- In the case of PERFECT-COLOR, the Structure paste must be mixed in **prior to hardening**.
- Finished Pearl structure lacquers can be diluted as necessary.

Note:

This information is for advice and based on the best knowledge available and careful research in line with current state of the art practice. This information cannot be held as legally binding. We also refer you to our terms and conditions of business.

The Material Safety Data Sheet according to the regulation (EC) No. 1907/2006 is available.

Status: 25 January 2023 1/1