

Trade name: Hesse COOL-COLOR, silky gloss PEX HB 65287-FT

Version: 5 / DK

Revision: 09.12.2022

Replaces Version: 4 / DK

Print date: 13.01.23

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Hesse COOL-COLOR, silky gloss PEX HB 65287-FT

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Hesse GmbH & Co. KG  
Warendorfer Strasse 21  
59075 Hamm (Germany)  
Telephone no. +49 (0) 2381 963-00  
Fax no. +49 (0) 2381 963-849  
E-mail address ps@hesse-lignal.de

### 1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612  
Testphrase

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

This product is not classified hazardous in accordance with Regulation (EC) No 1272/2008.

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

EUH208 Contains 2-methyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one, May produce an allergic reaction.

#### Supplemental information

EUH210 Safety data sheet available on request.

#### Further supplemental information

Young persons under 18 years may not work with this product.  
Contains 0,4 % of components with unknown hazards to the aquatic environment.

### 2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## SECTION 3: Composition/information on ingredients

### Hazardous ingredients

Trade name: Hesse COOL-COLOR, silky gloss PEX HB 65287-FT

Version: 5 / DK

Revision: 09.12.2022

Replaces Version: 4 / DK

Print date: 13.01.23

#### **1,2-benzisothiazol-3(2H)-one**

CAS No. 2634-33-5

EINECS no. 220-120-9

Concentration < 0,05 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4 H302

Skin Irrit. 2 H315

Eye Dam. 1 H318

Skin Sens. 1 H317

Aquatic Acute 1 H400

Aquatic Chronic 2 H411

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1 H317  $\geq 0,05$  %

#### **2-methyl-2H-isothiazol-3-one**

CAS No. 2682-20-4

EINECS no. 220-239-6

Concentration < 0,0015 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 3 H301

Acute Tox. 2 H330

Skin Corr. 1B H314

Aquatic Acute 1 H400

Aquatic Chronic 1 H410

Skin Sens. 1A H317

Acute Tox. 3 H311

Eye Dam. 1 H318

Route of exposure: Inhalation  
exposure

Concentration limits (Regulation (EC) No. 1272/2008)

Aquatic Acute 1 H400 M = 10

Skin Sens. 1A H317  $\geq 0,0015$  %

#### **Note**

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

### **4.1. Description of first aid measures**

#### **General information**

Remove affected person from danger area, lay him down. In all cases of doubt, or when symptoms persist, seek medical attention. Get medical advice/attention if you feel unwell. First aider: Pay attention to self-protection!

#### **After inhalation**

When spray fog inhaled, seek medical aid.

#### **After skin contact**

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

#### **After eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

Trade name: Hesse COOL-COLOR, silky gloss PEX HB 65287-FT

Version: 5 / DK

Revision: 09.12.2022

Replaces Version: 4 / DK

Print date: 13.01.23

### **After ingestion**

Do not induce vomiting. Take medical treatment.

### **4.2. Most important symptoms and effects, both acute and delayed**

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

### **4.3. Indication of any immediate medical attention and special treatment needed**

#### **Hints for the physician / treatment**

Treat symptomatically.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

#### **Non suitable extinguishing media**

Do not use a solid water stream as it may scatter and spread fire.

### **5.2. Special hazards arising from the substance or mixture**

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard.

### **5.3. Advice for firefighters**

#### **Special protective equipment for fire-fighting**

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

#### **Other information**

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Do not inhale vapours. Do not inhale gases. Do not inhale mist.

### **6.2. Environmental precautions**

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

### **6.4. Reference to other sections**

Refer to protective measures listed in Sections 7 and 8.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

Trade name: Hesse COOL-COLOR, silky gloss PEX HB 65287-FT

Version: 5 / DK

Revision: 09.12.2022

Replaces Version: 4 / DK

Print date: 13.01.23

### Advice on safe handling

Keep container tightly closed and dry in a cool, well-ventilated place. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

### Advice on protection against fire and explosion

Fight fire with normal precautions from a reasonable distance.

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

### Storage classes

Storage class according to TRGS 510      10      Flammable liquids

### Further information on storage conditions

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Other information

-

### 8.2. Exposure controls

#### Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

#### Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

#### Hand protection

Protective gloves complying with EN 374.

Glove material

Appropriate Material      butyl-rubber

Material thickness       $\geq$       0,5      mm

Breakthrough time       $\geq$       120      min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.



Trade name: Hesse COOL-COLOR, silky gloss PEX HB 65287-FT

Version: 5 / DK

Revision: 09.12.2022

Replaces Version: 4 / DK

Print date: 13.01.23

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Eye protection

Wear eye glasses with side protection according to EN 166.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

liquid

#### Colour

coloured

#### Odour

characteristic

#### Melting point

Remarks not determined

#### Freezing point

Remarks not determined

#### Boiling point or initial boiling point and boiling range

Value 100 to 170 °C

#### Flammability

not determined

#### Upper and lower explosive limits

Remarks not determined

#### Flash point

Value > 60 °C

#### Ignition temperature

Remarks not determined

#### Decomposition temperature

Remarks not determined

#### pH value

Value 8  
Concentration/H<sub>2</sub>O 100

#### Viscosity

Remarks not determined

#### Solubility(ies)

Remarks not determined

#### Partition coefficient n-octanol/water (log value)

Remarks not determined

#### Vapour pressure

Remarks not determined

#### Density and/or relative density

Value appr. 1,044 kg/l  
Temperature 20 °C

Trade name: Hesse COOL-COLOR, silky gloss PEX HB 65287-FT

Version: 5 / DK

Revision: 09.12.2022

Replaces Version: 4 / DK

Print date: 13.01.23

**Relative vapour density**

Remarks not determined

**Particle characteristics**

Remarks not determined

**9.2. Other information**

**Odour threshold**

Remarks not determined

**Solubility in water**

Remarks not determined

**Efflux time**

Value 26 to 40 s  
Temperature 20 °C  
Method DIN 53211 - 6 mm

**Explosive properties**

evaluation not determined

**Oxidising properties**

Remarks not determined

**Non-volatile content**

Value 39,8 %  
Method calculated value

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Stable under recommended storage and handling conditions (see section 7).

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

To avoid thermal decomposition, do not overheat.

**10.4. Conditions to avoid**

Isolate from sources of heat, sparks and open flame.

**10.5. Incompatible materials**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.6. Hazardous decomposition products**

Carbon monoxide and carbon dioxide, nitrous oxides (NO<sub>x</sub>), dense black smoke, No decomposition if used as prescribed.

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute oral toxicity**

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

Trade name: Hesse COOL-COLOR, silky gloss PEX HB 65287-FT

Version: 5 / DK

Revision: 09.12.2022

Replaces Version: 4 / DK

Print date: 13.01.23

### Acute oral toxicity (Components)

#### 2-methyl-2H-isothiazol-3-one

Species	rat		
LD50		120	mg/kg
Method	EPA		
Source	1 (reliable without restriction)		

#### 1,2-benzisothiazol-3(2H)-one

Species	rat		
LD50		1193	mg/kg

### Acute dermal toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

### Acute dermal toxicity (Components)

#### 2-methyl-2H-isothiazol-3-one

Species	rat		
LD50		242	mg/kg
Source	1 (reliable without restriction)		

### Acute inhalational toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

### Acute inhalative toxicity (Components)

#### 2-methyl-2H-isothiazol-3-one

Species	rat		
LC50		0,1	mg/l
Duration of exposure		4	h
Administration/Form	Dust/Mist		
Source	1 (reliable without restriction)		

### Skin corrosion/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

### Skin corrosion/irritation (Components)

#### 2-methyl-2H-isothiazol-3-one

evaluation	Causes burns.
------------	---------------

#### 1,2-benzisothiazol-3(2H)-one

evaluation	Irritating to skin.
------------	---------------------

### Serious eye damage/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

### Serious eye damage/irritation (Components)

#### 2-methyl-2H-isothiazol-3-one

evaluation	Causes severe caustic burns to skin and eyes.
------------	---

#### 1,2-benzisothiazol-3(2H)-one

evaluation	Irritating to eyes.
------------	---------------------

### Sensitization

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Trade name: Hesse COOL-COLOR, silky gloss PEX HB 65287-FT

Version: 5 / DK

Revision: 09.12.2022

Replaces Version: 4 / DK

Print date: 13.01.23

## Sensitization (Components)

### 2-methyl-2H-isothiazol-3-one

evaluation

May cause sensitization by skin contact.

### 1,2-benzisothiazol-3(2H)-one

Reference substance

1,2-benzisothiazol-3(2H)-one

evaluation

May cause sensitization by skin contact.

## Mutagenicity

Method

Calculation method (Regulation (EC) No. 1272/2008)

Remarks

Based on available data, the classification criteria are not met.

## Reproductive toxicity

Method

Calculation method (Regulation (EC) No. 1272/2008)

Remarks

Based on available data, the classification criteria are not met.

## Carcinogenicity

Method

Calculation method (Regulation (EC) No. 1272/2008)

Remarks

Based on available data, the classification criteria are not met.

## Specific Target Organ Toxicity (STOT)

### Single exposure

Method

Calculation method (Regulation (EC) No. 1272/2008)

Remarks

Based on available data, the classification criteria are not met.

### Repeated exposure

Remarks

Based on available data, the classification criteria are not met.

## Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2 Information on other hazards

### Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

### Other information

No toxicological data are available.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Fish toxicity (Components)

##### 1,2-benzisothiazol-3(2H)-one

Species

Oncorhynchus mykiss (rainbow trout)

LC50

2,18

mg/l

Duration of exposure

96

h

#### Daphnia toxicity (Components)

##### 2-methyl-2H-isothiazol-3-one

Species

Daphnia magna (Water flea)

NOEC

0,044

mg/l

Duration of exposure

21

d



Trade name: Hesse COOL-COLOR, silky gloss PEX HB 65287-FT

Version: 5 / DK

Revision: 09.12.2022

Replaces Version: 4 / DK

Print date: 13.01.23

#### **1,2-benzisothiazol-3(2H)-one**

Species	Daphnia magna (Water flea)	
EC50	2,94	mg/l
Duration of exposure	48	h

#### **Algae toxicity (Components)**

##### **2-methyl-2H-isothiazol-3-one**

EC50	0,157	mg/l
Duration of exposure	96	h

### **12.2. Persistence and degradability**

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

#### **Biodegradability (Components)**

##### **2-methyl-2H-isothiazol-3-one**

evaluation Readily biodegradable.

##### **1,2-benzisothiazol-3(2H)-one**

evaluation Readily biodegradable.

### **12.3. Bioaccumulative potential**

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

#### **Partition coefficient n-octanol/water (log value)**

Remarks not determined

### **12.4. Mobility in soil**

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

#### **Mobility in soil**

no data available

### **12.5. Results of PBT and vPvB assessment**

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

#### **Results of PBT and vPvB assessment**

The product contains no PBT substances

The product contains no vPvB substances.

### **12.6 Endocrine disrupting properties**

#### **Endocrine disrupting properties with respect to the environment**

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

### **12.7. Other adverse effects**

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

## **SECTION 13: Disposal considerations**

Trade name: Hesse COOL-COLOR, silky gloss PEX HB 65287-FT

Version: 5 / DK

Revision: 09.12.2022

Replaces Version: 4 / DK

Print date: 13.01.23

### 13.1. Waste treatment methods

#### Disposal recommendations for the product

EWC waste code 080111 - waste paint and varnish containing organic solvents or other dangerous substances

EWC waste code 200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

#### modified product

EWC waste code 080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

#### Dried residues

EWC waste code 080112 - waste lacquers and waste paint except those falling under 080111

#### Disposal recommendations for packaging

EWC waste code 150110 - packaging containing residues of or contaminated by dangerous substances

Completely emptied packagings can be given for recycling.

### SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	Not classified as dangerous in the meaning of transport regulations.	Not classified as dangerous in the meaning of sea and air transport regulations.	Not a dangerous substance as defined in the above regulations.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### VOC

VOC (EU) 0,9 % 10 g/l

##### MAL-Code

MAL-Code 1-1  
MAL 120,32 m³/l

### SECTION 16: Other information

#### Hazard statements listed in Chapter 3

H301 Toxic if swallowed.  
H302 Harmful if swallowed.  
H311 Toxic in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.

Trade name: Hesse COOL-COLOR, silky gloss PEX HB 65287-FT

Version: 5 / DK

Revision: 09.12.2022

Replaces Version: 4 / DK

Print date: 13.01.23

H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

### **CLP categories listed in Chapter 3**

Acute Tox. 2	Acute toxicity, Category 2
Acute Tox. 3	Acute toxicity, Category 3
Acute Tox. 4	Acute toxicity, Category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Eye Dam. 1	Serious eye damage, Category 1
Skin Corr. 1B	Skin corrosion, Category 1B
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1A	Skin sensitization, Category 1A

### **Abbreviations**

ADR - Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IMDG - International Maritime Code for Dangerous Goods  
IATA - International Air Transport Association  
IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
GHS - Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS - European Inventory of Existing Commercial Chemical Substances  
CAS - Chemical Abstracts Service (division of the American Chemical Society)  
GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)  
LOAEL - Lowest Observed Adverse Effect Level  
LOEL - Lowest Observed Effect Level  
NOAEL - No Observed Adverse Effect Level  
NOEC - No Observed Effect Concentration  
NOEL - No Observed Effect Level  
OECD - Organisation for Economic Cooperation and Development  
VOC - Volatile Organic Compounds  
Changes since the last version are highlighted in the margin (\*\*\*). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.