

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Hesse HYDRO Glaze stain PEX BO XX-FT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Surface treatment of wood and other materials

Identified Uses

	REACHSET 1000
SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROC7	Industrial spraying

	REACHSET 2001
SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC11	Non industrial spraying

	REACHSET 2003
SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC10	Roller application or brushing

	REACHSET 3001
SU21	Consumer uses: Private households (= general public = consumers)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC11	Non industrial spraying

	REACHSET 3003
SU21	Consumer uses: Private households (= general public = consumers)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC10	Roller application or brushing

1.3. Details of the supplier of the safety data sheet

Manufacturer

Hesse GmbH & Co. KG
Warendorfer Strasse 21
59075 Hamm (Germany)

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

Telephone no. +49 (0) 2381 963-00
Fax no. +49 (0) 2381 963-849
E-mail address ps@hesse-lignal.de

1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612
Testphrase

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)
Skin Sens. 1A H317

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008
For explanation of abbreviations see section 16.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Warning

Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains 2-methyl-2H-isothiazol-3-one; 1,2-benzisothiazol-3(2H)-one

Supplemental information

Further supplemental information

Young persons under 18 years may not work with this product.

2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

SECTION 3: Composition/information on ingredients

Hazardous ingredients

1,2-benzisothiazol-3(2H)-one

CAS No.	2634-33-5			
EINECS no.	220-120-9			
Concentration		<	0,05	%
Classification (Regulation (EC) No. 1272/2008)				
	Acute Tox. 4		H302	
	Skin Irrit. 2		H315	
	Eye Dam. 1		H318	
	Skin Sens. 1		H317	
	Aquatic Acute 1		H400	
	Aquatic Chronic 2		H411	

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1 H317 $\geq 0,05$ %

2-methyl-2H-isothiazol-3-one

CAS No.	2682-20-4			
EINECS no.	220-239-6			
Concentration	$\geq 0,01$	<	0,1	%
Classification (Regulation (EC) No. 1272/2008)				
	Acute Tox. 3		H301	
	Acute Tox. 2		H330	
	Skin Corr. 1B		H314	
	Aquatic Acute 1		H400	
	Aquatic Chronic 1		H410	
	Skin Sens. 1A		H317	
	Acute Tox. 3		H311	
	Eye Dam. 1		H318	

Route of exposure: Inhalation
exposure

Concentration limits (Regulation (EC) No. 1272/2008)

Aquatic Acute 1 H400 M = 10
Skin Sens. 1A H317 $\geq 0,0015$ %

Note

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from danger area, lay him down. In all cases of doubt, or when symptoms persist, seek medical attention. Get medical advice/attention if you feel unwell. First aider: Pay attention to self-protection!

After inhalation

When spray fog inhaled, seek medical aid.

After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

After ingestion

Do not induce vomiting. Take medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / treatment

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO₂, powders, water spray/mist

Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard.

5.3. Advice for firefighters

Special protective equipment for fire-fighting

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

Other information

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Do not inhale vapours. Do not inhale gases. Do not inhale mist.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed and dry in a cool, well-ventilated place. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

Advice on protection against fire and explosion

Fight fire with normal precautions from a reasonable distance.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Storage classes

Storage class according to TRGS 510 10 Flammable liquids

Further information on storage conditions

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Other information

-

8.2. Exposure controls

Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Protective gloves complying with EN 374.

Glove material

Appropriate Material butyl-rubber

Material thickness \geq 0,5 mm

Breakthrough time \geq 120 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Eye protection

Wear eye glasses with side protection according to EN 166.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid

Colour coloured

Odour characteristic

Melting point

Remarks not determined

Freezing point

Remarks not determined

Boiling point or initial boiling point and boiling range

Value 100 to 189 °C

Flammability

not determined

Upper and lower explosive limits

Remarks not determined

Flash point

Value > 60 °C

Ignition temperature

Remarks not determined

Decomposition temperature

Remarks not determined

pH value

Value 8

Concentration/H₂O 100

Viscosity

Remarks not determined

Solubility(ies)

Remarks not determined

Partition coefficient n-octanol/water (log value)

Remarks not determined

Vapour pressure

Remarks not determined

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

Density and/or relative density

Value	appr. 1,026		kg/l
Temperature	20	°C	

Relative vapour density

Remarks	not determined
---------	----------------

Particle characteristics

Remarks	not determined
---------	----------------

9.2. Other information

Odour threshold

Remarks	not determined
---------	----------------

Solubility in water

Remarks	not determined
---------	----------------

Efflux time

Value	20	to	48	s
Temperature	20	°C		
Method	DIN EN ISO 2431 - 3 mm			

Explosive properties

evaluation	not determined
------------	----------------

Oxidising properties

Remarks	not determined
---------	----------------

Non-volatile content

Value	19	%
-------	----	---

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under recommended storage and handling conditions (see section 7).

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide, nitrous oxides (NO_x), dense black smoke, No decomposition if used as prescribed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

Acute oral toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Acute oral toxicity (Components)

1,2-benzisothiazol-3(2H)-one

Species	rat	
LD50	1193	mg/kg

2-methyl-2H-isothiazol-3-one

Species	rat	
LD50	120	mg/kg
Method	EPA	
Source	1 (reliable without restriction)	

Acute dermal toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Acute dermal toxicity (Components)

2-methyl-2H-isothiazol-3-one

Species	rat	
LD50	242	mg/kg
Source	1 (reliable without restriction)	

Acute inhalational toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Acute inhalative toxicity (Components)

2-methyl-2H-isothiazol-3-one

Species	rat	
LC50	0,1	mg/l
Duration of exposure	4	h
Administration/Form	Dust/Mist	
Source	1 (reliable without restriction)	

Skin corrosion/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Skin corrosion/irritation (Components)

1,2-benzisothiazol-3(2H)-one

evaluation	Irritating to skin.
------------	---------------------

2-methyl-2H-isothiazol-3-one

evaluation	Causes burns.
------------	---------------

Serious eye damage/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Serious eye damage/irritation (Components)

1,2-benzisothiazol-3(2H)-one

evaluation	Irritating to eyes.
------------	---------------------

2-methyl-2H-isothiazol-3-one

evaluation	Causes severe caustic burns to skin and eyes.
------------	---

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

Sensitization

evaluation	May cause sensitization by skin contact.
Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	The classification criteria are met.

Sensitization (Components)

1,2-benzisothiazol-3(2H)-one

Reference substance	1,2-benzisothiazol-3(2H)-one
evaluation	May cause sensitization by skin contact.

2-methyl-2H-isothiazol-3-one

evaluation	May cause sensitization by skin contact.
------------	--

Mutagenicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Reproductive toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Carcinogenicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)

Single exposure

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Repeated exposure

Remarks	Based on available data, the classification criteria are not met.
---------	---

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

Other information

No toxicological data are available.

SECTION 12: Ecological information

12.1. Toxicity

General information

For this subsection there is no ecotoxicological data available on the product as such.

Fish toxicity (Components)

1,2-benzisothiazol-3(2H)-one

Species	Oncorhynchus mykiss (rainbow trout)	
LC50	2,18	mg/l
Duration of exposure	96	h

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

Daphnia toxicity (Components)

1,2-benzisothiazol-3(2H)-one

Species	Daphnia magna (Water flea)	
EC50	2,94	mg/l
Duration of exposure	48	h

2-methyl-2H-isothiazol-3-one

Species	Daphnia magna (Water flea)	
NOEC	0,044	mg/l
Duration of exposure	21	d

Algae toxicity (Components)

2-methyl-2H-isothiazol-3-one

EC50	0,157	mg/l
Duration of exposure	96	h

12.2. Persistence and degradability

General information

For this subsection there is no ecotoxicological data available on the product as such.

Biodegradability (Components)

1,2-benzisothiazol-3(2H)-one

evaluation Readily biodegradable.

2-methyl-2H-isothiazol-3-one

evaluation Readily biodegradable.

12.3. Bioaccumulative potential

General information

For this subsection there is no ecotoxicological data available on the product as such.

Partition coefficient n-octanol/water (log value)

Remarks not determined

12.4. Mobility in soil

General information

For this subsection there is no ecotoxicological data available on the product as such.

Mobility in soil

no data available

12.5. Results of PBT and vPvB assessment

General information

For this subsection there is no ecotoxicological data available on the product as such.

Results of PBT and vPvB assessment

The product contains no PBT substances
The product contains no vPvB substances.

12.6 Endocrine disrupting properties

Endocrine disrupting properties with respect to the environment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

General information

For this subsection there is no ecotoxicological data available on the product as such.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

EWC waste code 080111 - waste paint and varnish containing organic solvents or other dangerous substances

EWC waste code 200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.
Do not allow to enter drains or waterways.

modified product

EWC waste code 080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

Dried residues

EWC waste code 080112 - waste lacquers and waste paint except those falling under 080111

Disposal recommendations for packaging

EWC waste code 150110 - packaging containing residues of or contaminated by dangerous substances

Completely emptied packagings can be given for recycling.

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	Not classified as dangerous in the meaning of transport regulations.	Not classified as dangerous in the meaning of sea and air transport regulations.	Not a dangerous substance as defined in the above regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC

VOC (EU) appr. 0,3 % 4 g/l

MAL-Code

MAL-Code 1-1
MAL 143,96 m³/l

Other information

All components are contained in the IECSC inventory.

SECTION 16: Other information

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

Hazard statements listed in Chapter 3

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

CLP categories listed in Chapter 3

Acute Tox. 2	Acute toxicity, Category 2
Acute Tox. 3	Acute toxicity, Category 3
Acute Tox. 4	Acute toxicity, Category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Eye Dam. 1	Serious eye damage, Category 1
Skin Corr. 1B	Skin corrosion, Category 1B
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1A	Skin sensitization, Category 1A

Abbreviations

ADR - Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG - International Maritime Code for Dangerous Goods
IATA - International Air Transport Association
IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS - Globally Harmonized System of Classification and Labelling of Chemicals
EINECS - European Inventory of Existing Commercial Chemical Substances
CAS - Chemical Abstracts Service (division of the American Chemical Society)
GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
LOAEL - Lowest Observed Adverse Effect Level
LOEL - Lowest Observed Effect Level
NOAEL - No Observed Adverse Effect Level
NOEC - No Observed Effect Concentration
NOEL - No Observed Effect Level
OECD - Organisation for Economic Cooperation and Development
VOC - Volatile Organic Compounds
Changes since the last version are highlighted in the margin (***). This version replaces all previous versions.
This safety datasheet only contains information relating to safety and does not replace any product information or product specification.
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.

Annex to the extended Safety Data Sheet (eSDS)

Short title of the exposure scenario

ES017 - Industrial applications: industrial spraying (inside)

Use of the substance/preparation

Surface treatment of wood and other materials

Use

SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROC7	Industrial spraying

Contributing exposure scenario controlling environmental exposure

Use

ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix

Physical form

liquid

Maximum amount used per time or activity

Emission days per site: <= 300

Other relevant operational conditions

Use: Room temperature
Drying and through-curing takes place at ambient temperature or at higher temperatures.
Curing takes place through UV light exposure (only with UV light curing systems).
Where possible recycling is preferred to disposal or incineration.
Do not allow to enter soil, waterways or waste water canal.
Dispose of rinse water in accordance with local and national regulations.

Waste water

Do not discharge into the drains/surface waters/groundwater. Spray cabin waters are to be conducted after mechanical pretreatment into a wastewater treatment facility.

Exhaust air

Keep container closed. Avoid release to the environment.

Soil

Floors should be impervious, resistant to liquids and easy to clean.

Disposal recommendations for the product

EWC waste code	080111 - waste paint and varnish containing organic solvents or other dangerous substances
	200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

Do not allow to enter drains or waterways.

modified product

EWC waste code 080115 - aqueous sludges containing paint or varnish
containing organic solvents or other dangerous substances

Dried residues

EWC waste code 080112 - waste lacquers and waste paint except those falling
under 080111

Disposal recommendations for packaging

EWC waste code 150110 - packaging containing residues of or contaminated
by dangerous substances
Completely emptied packagings can be given for recycling.

Contributing exposure scenario controlling worker exposure

Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
PROC7 Industrial spraying

Physical form

liquid

Maximum amount used per time or activity

Duration of exposure	<=	8	h/d
Frequency of exposure	<=	220	d/a

Other relevant operational conditions

Use: Room temperature
Drying and through-curing takes place at ambient temperature or at higher temperatures.
Curing takes place through UV light exposure (only with UV light curing systems).
Read attached instructions before use.

Product substance and product safety related measures

Mainly used in closed systems. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.
Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Protective gloves complying with EN 374.

Glove material

Appropriate Material butyl-rubber

Material thickness >= 0,5

Breakthrough time >= 120

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Eye protection

Wear eye glasses with side protection according to EN 166.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

Information on estimated exposure and downstream-user guidance

Guidance for Downstream Users

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.

Annex to the extended Safety Data Sheet (eSDS)

Short title of the exposure scenario

ES019 - Professional uses: Non industrial spraying (inside)

Use of the substance/preparation

Surface treatment of wood and other materials

Use

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC11	Non industrial spraying

Contributing exposure scenario controlling environmental exposure

Use

ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix

Physical form

liquid

Maximum amount used per time or activity

Emission days per site: <= 250

Other relevant operational conditions

Use: Room temperature
Drying and through-curing takes place at ambient temperature or at higher temperatures.
Curing takes place through UV light exposure (only with UV light curing systems).
Where possible recycling is preferred to disposal or incineration.
Do not allow to enter soil, waterways or waste water canal.
Dispose of rinse water in accordance with local and national regulations.

Waste water

Do not discharge into the drains/surface waters/groundwater.

Exhaust air

Keep container closed. Avoid release to the environment.

Soil

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

Floors should be impervious, resistant to liquids and easy to clean.

Disposal recommendations for the product

EWC waste code 080111 - waste paint and varnish containing organic solvents or other dangerous substances
200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

modified product

EWC waste code 080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

Dried residues

EWC waste code 080112 - waste lacquers and waste paint except those falling under 080111

Disposal recommendations for packaging

EWC waste code 150110 - packaging containing residues of or contaminated by dangerous substances

Completely emptied packagings can be given for recycling.

Contributing exposure scenario controlling worker exposure (professional)

Short title of the exposure scenario

Substance number:CES038

Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

PROC11 Non industrial spraying

Physical form

liquid

Maximum amount used per time or activity

Duration of exposure	<=	8	h/d
Frequency of exposure	<=	220	d/a

Other relevant operational conditions

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Curing takes place through UV light exposure (only with UV light curing systems).

Read attached instructions before use.

Product substance and product safety related measures

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.

Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Protective gloves complying with EN 374.

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

Glove material
Appropriate Material butyl-rubber
Material thickness \geq 0,5
Breakthrough time \geq 120

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Eye protection

Wear eye glasses with side protection according to EN 166.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

Information on estimated exposure and downstream-user guidance

Guidance for Downstream Users

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.

Annex to the extended Safety Data Sheet (eSDS)

Short title of the exposure scenario

ES020 - Professional uses: roller application or brushing, dipping and pouring and other processing without aerosol formation (inside)

Use of the substance/preparation

Surface treatment of wood and other materials

Use

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROCh01	Other processing without aerosol formation
PROC13	Treatment of articles by dipping and pouring
PROC10	Roller application or brushing

Contributing exposure scenario controlling environmental exposure

Use

ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix

Physical form liquid

Maximum amount used per time or activity

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

Emission days per site: <= 250

Other relevant operational conditions

Use: Room temperature
Drying and through-curing takes place at ambient temperature or at higher temperatures.
Curing takes place through UV light exposure (only with UV light curing systems).
Where possible recycling is preferred to disposal or incineration.
Do not allow to enter soil, waterways or waste water canal.
Dispose of rinse water in accordance with local and national regulations.

Waste water

Do not discharge into the drains/surface waters/groundwater.

Exhaust air

Keep container closed. Avoid release to the environment.

Soil

Floors should be impervious, resistant to liquids and easy to clean.

Disposal recommendations for the product

EWC waste code	080111 - waste paint and varnish containing organic solvents or other dangerous substances
	200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.
Do not allow to enter drains or waterways.

modified product

EWC waste code	080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances
----------------	--

Dried residues

EWC waste code	080112 - waste lacquers and waste paint except those falling under 080111
----------------	---

Disposal recommendations for packaging

EWC waste code	150110 - packaging containing residues of or contaminated by dangerous substances
----------------	---

Completely emptied packagings can be given for recycling.

Contributing exposure scenario controlling worker exposure (professional)

Short title of the exposure scenario

Substance number:CES040

Use

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
PROCh01	Other processing without aerosol formation
PROC10	Roller application or brushing
PROC13	Treatment of articles by dipping and pouring

Physical form

liquid

Maximum amount used per time or activity

Duration of exposure	<=	8	h/d
Frequency of exposure	<=	220	d/a

Other relevant operational conditions

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Curing takes place through UV light exposure (only with UV light curing systems).

Read attached instructions before use.

Product substance and product safety related measures

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.

Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Protective gloves complying with EN 374.

Glove material

Appropriate Material butyl-rubber

Material thickness \geq 0,5

Breakthrough time \geq 120

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Eye protection

Wear eye glasses with side protection according to EN 166.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

Information on estimated exposure and downstream-user guidance

Guidance for Downstream Users

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.

Annex to the extended Safety Data Sheet (eSDS)

Short title of the exposure scenario

ES040 - Private households (= general public = consumers): roller application or brushing, dipping and pouring, non industrial spraying and other processing without aerosol formation (inside)

Use of the substance/preparation

Surface treatment of wood and other materials

Print date: 14.02.23

SU21	Consumer uses: Private households (= general public = consumers)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROCh01	Other processing without aerosol formation
PROC10	Roller application or brushing
PROC11	Non industrial spraying
PROC13	Treatment of articles by dipping and pouring

ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix

liquid

Emission days per site: <= 20 d

Use: Room temperature
Adhere to the recommended processing temperature.
Volatile organic substances will volatilise into the atmospheric air inside.
Do not allow to enter soil, waterways or waste water canal.

Do not discharge into the drains/surface waters/groundwater.

No special measures required.

Floors should be impervious, resistant to liquids and easy to clean. Protect floor with suitable covering plastic film / paper.

EWC waste code 080111 - waste paint and varnish containing organic solvents
or other dangerous substances
200127 - paint, inks, adhesives and resins containing
dangerous substances

Where possible recycling is preferred to disposal or incineration.
Do not allow to enter drains or waterways.

EWC waste code	080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances
----------------	--

EWC waste code	080112 - waste lacquers and waste paint except those falling under 080111
----------------	---

EWK waste code 150110 - packaging containing residues of or contaminated by dangerous substances

Completely emptied packagings can be given for recycling.

Trade name: Hesse HYDRO Glaze stain PEX BO XX-FT

Version: 13 / DK

Revision: 18.01.2023

Replaces Version: 12 / DK

Print date: 14.02.23

Contributing exposure scenario controlling consumer exposure

Use

SU21	Consumer uses: Private households (= general public = consumers)
PROCh01	Other processing without aerosol formation
PROC10	Roller application or brushing
PROC11	Non industrial spraying
PROC13	Treatment of articles by dipping and pouring

Physical form

liquid

Maximum amount used per time or activity

Duration of exposure	<=	4	h/d
Frequency of exposure	<=	20	d/a

Other relevant operational conditions

Use: Room temperature
Drying and through-curing takes place at ambient temperature or at higher temperatures.
Adhere to the recommended processing temperature.
Volatile organic substances will volatilise into the atmospheric air inside.

Product substance and product safety related measures

Keep out of reach of children. Wash hands before breaks and after work. Do not eat, drink or smoke when using this product.

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.

Recommended Filter type: Respiratory protection mask with combination filter A/P2

Protective gloves complying with EN 374.

Glove material

Appropriate Material butyl-rubber

Material thickness >= 0,5

Breakthrough time >= 120

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Wear eye glasses with side protection according to EN 166.

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

Information on estimated exposure and downstream-user guidance

Guidance for Downstream Users

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.